

60/61/62/63-1
Seat w/ legs

Configuration 60, 61, 62, 63
WITH LEGS

Folding Shower Seats

with Padded Surface

Architectural, Commercial,
Institutional, Residential

PADDED SEAT

SPECIFICATION:

Folding shower seat from 1" (25mm) diameter, 18 gauge and 1 1/4" (32mm) X 1 1/4" (32mm), 16 gauge, type 304 stainless steel tubing with #4 satin finish. Wall mount brackets shall be 12 gauge type 304 stainless steel. Padded vinyl cushion shall have 1 1/2" (38mm) high density, high resilience foam, covered with fire and mildew resistant, UV inhibited, marine grade naugahyde. Waterproof Seam Cushions shall have no external piping. Seat unit shall comply with all applicable federal provincial and local building and safety codes.



Custom sizes are available to suit special requirements.

26" X 21" (660 X 530 mm) seat	White
26" X 21" (660 X 530 mm) seat	Almond
28" X 21" (710 X 530 mm) seat	White
28" X 21" (710 X 530 mm) seat	Almond
30" X 21" (760 X 530 mm) seat	White
30" X 21" (760 X 530 mm) seat	Almond
32" X 21" (810 X 530 mm) seat	White
32" X 21" (810 X 530 mm) seat	Almond

Adult Shower Seats have been designed and tested to withstand 400lbs. (182kg) * of load capacity when properly installed. This exceeds HUD, FHA, VA, ADA, ANSI and other federal, provincial, and local codes. * The Junior Folding Shower Seat has been designed and tested to withstand 250lbs (114kg).

