



60/61/62/63-2  
Seat w/ legs

Configuration 60, 61, 62, 63  
WITH LEGS

# Folding Shower Seats

*with Phenolic Surface*

Architectural, Commercial,  
Institutional, Residential

## PHENOLIC SEAT

### SPECIFICATION:

from 1" (25mm) diameter,  
18 gauge and 1 1/4" (32mm) X 1 1/4"  
(32mm), 16 gauge, type 304 stainless  
steel tubing with #4 satin finish. Wall  
mount brackets shall be 12 gauge type  
304 stainless steel. Solid Phenolic seat  
slats shall be 1/2" (13mm) thick and  
4 7/16" (111mm) wide and shall be  
fire and mildew resistant. Seat unit  
shall comply with all applicable  
federal provincial and local building  
and safety codes.



### Custom sizes are available to suit special requirements.

|                               |           |
|-------------------------------|-----------|
| 26" X 21" (660 X 530 mm) seat | White     |
| 26" X 21" (660 X 530 mm) seat | Woodgrain |
| 28" X 21" (710 X 530 mm) seat | White     |
| 28" X 21" (710 X 530 mm) seat | Woodgrain |
| 30" X 21" (760 X 530 mm) seat | White     |
| 30" X 21" (760 X 530 mm) seat | Woodgrain |
| 32" X 21" (810 X 530 mm) seat | White     |
| 32" X 21" (810 X 530 mm) seat | Woodgrain |

Adult Shower Seats have been designed and tested to withstand 400lbs.  
(182kg) \* of load capacity when properly installed. This exceeds HUD, FHA, VA, ADA, ANSI  
and other federal, provincial, and local codes. \* The Junior Folding Shower Seat has been  
designed and tested to withstand 250lbs (114kg).

