

Flip Up Tub Seats

Phenolic

Configuration:

70 Series

Phenolic

Application Use:

Architectural

Commercial

Institutional

Residential

Specifications

Folding tub seat manufactured from 1" (25mm) diameter, 18 gauge, type 304 stainless steel tubing with #4 satin finish. Hinged mounting brackets shall be 12 gauge type 304 stainless steel. Hooks firmly into place when in the up position to be stored safely out of the way. Solid Phenolic seat shall be 1/2" (13mm) thick and shall be fire and mildew resistant. Shower Seat shall comply with all applicable federal, provincial and local building and safety codes.



Woodgrain shown, Also available in White

Custom sizes are available to suit special requirements.

15" x 28"	(381mm x 711mm)	White	Model # 70-PA152801
15" x 28"	(381mm x 711mm)	Woodgrain	Model # 70-PH152815
15" x 32"	(381mm x 812mm)	White	Model # 70-PH153201
15" x 32"	(381mm x 812mm)	Woodgrain	Model # 70-PH153215

Shower Seats have been designed and tested to withstand 250lbs. (114kgs) of load when properly installed.* This exceeds HUD, FHA, VA, ADA, ANSI and other federal, provincial, and local codes. *Shower seats can only be as strong as what they are mounted to. It is imperative when installing any shower seat to consult with a qualified contractor to insure you have sufficient backing.

